



PIN	A	B	C
2	9.85	3.00	13.23
3	12.85	6.00	16.23
4	15.85	9.00	19.23
5	18.85	12.00	22.23
6	21.85	15.00	25.23
7	24.85	18.00	28.23
8	27.85	21.00	31.23
9	30.85	24.00	34.23
10	33.85	27.00	37.23
11	36.85	30.00	40.23
12	39.85	33.00	43.23

一. 电气性能:

1-1. 额定电流: 3A AC DC.

1-2. 接触电阻:  $\leq 20m\Omega$

1-3. 绝缘电阻:  $\geq 1000M\Omega$

1-4. 耐压: 550V AC/Minute

二. 物理特性:

2-1. 操作温度:  $-55^{\circ}C \sim 105^{\circ}C$

2-2. 焊接温度:  $+240^{\circ}C$ , 8s max

三. 材质:

3-1. 塑胶: PA46 (Black) UL94V-0

3-2. 插针: Brass/Gold plated

P.C.B. Layout

巨赛实业(深圳)有限公司  
JUSAI INDUSTRIAL (SHENZHEN) CO.,LTD

图名: VF3.0-LT-2xNA

图号: XXXXXXXXXXXXXXXXXXXXXXX

未标注公差	
XX.	$\pm 0.40$
X.	$\pm 0.30$
.XX	$\pm 0.20$
.XX	$\pm 0.15$

绘制:

签发:

审核:

单位: MM

比例: 1:1

视图: