



技术参数 SPECIFICATIONS

- ◆ 极数: 2\*22 Poles: 2\*22
- ◆ 额定电压: DC, 30V(50HZ有效值) Voltage rating: DC, 30V(50HZ)
- ◆ 额定电流: 0.2A, DC (AWG332) Current rating: 0.2A, DC (AWG332)
- ◆ 额定电流: 0.5A, DC (AWG336) Current rating: 0.5A, DC (AWG336)
- ◆ 耐压值: 200V AC/minute Withstand voltage: 200V AC/minute
- ◆ 工作温度: -25℃~+85℃ Working Temperature: -25℃~+85℃
- ◆ 绝缘电阻: > 100 Moh Insulation resistance: > 100 Moh
- ◆ 接触电阻: < 0.02 oh Contact resistance: < 0.02 oh
- ◆ 壳体材料 (TERMINAL) 材质: 磷青铜 Material: Phosphor Bronze
- ◆ 塑胶本体 (HOUSING) 材质: 热塑性塑料, UL 94V-0 Material: Thermoplastic, UL94-0

包装方式 PACKAGE

- ◆ 管装 Pipe Package
- ◆ 带装 Tape and Reel Package
- ◆ 袋装 Bag Package

NO. of Contacts (n)	Dimensions			
	A	B	C	D
2	0.8	3.8	3.0	4.6
3	1.6	4.6	3.8	5.4
4	2.4	5.4	4.6	6.2
5	3.2	6.2	5.4	7.0
6	4.0	7.0	6.2	7.8
7	4.8	7.8	7.0	8.6
8	5.6	8.6	7.8	9.4
9	7.2	9.4	8.6	10.2
10	8.0	10.2	9.4	11.0
11	8.8	11.0	10.2	11.8
12	9.6	11.8	11.0	12.6
13	10.4	12.6	11.8	13.4
14	11.2	13.4	12.6	14.2
15	12.0	14.2	13.4	15.0
16	12.8	15.0	14.2	15.8
17	13.6	15.8	15.0	16.6
18	14.4	16.6	15.8	17.4
19	15.2	17.4	16.6	18.2
20	16.0	18.2	17.4	19.0
21	16.8	19.0	18.2	19.8
22	17.6	19.8	19.0	20.6

GENERAL TOLERANCES		SCALE	DRAWN	DATE	DWG. NO.	TITLE	REV.
XL ± 0.25	XXL ± 0.40	5:1	CHECK	DATE	0.8T-1-nAB	成品图	B
X ± 0.20	.XXI ± 0.02	MM	APPROVE	DATE			PARTS NO.
.Y ± 0.15	.Y' ± 0.2°	MM					1/1
.X ± 0.05	.Y' ± 0.1°	A4					

www.szjusun.cn