



■ 技术参数 SPECIFICATIONS

- ◆ 适用线规: AWG#28~#30
- ◆ Applicable Wire: AWG#28~#30
- ◆ 额定电压: 125V DC,AC(rms)
- ◆ Rated voltage: 125V DC,AC(rms)
- ◆ 额定电流: 1.0A (max.)
- ◆ Rated Current: 1.0A (max.)
- ◆ 耐压值: 250V AC/minute
- ◆ Withstand voltage: 250V AC/min.
- ◆ 工作温度: -40°C ~ +85°C
- ◆ Working Temp: -40°C ~ +85°C
- ◆ 绝缘电阻: ≥500 MΩ
- ◆ Insulation resistance: ≥500 MΩ
- ◆ 接触电阻: ≤20 mΩ
- ◆ Contact resistance: ≤20 mΩ

■ 材料 MATERIAL

- ◆ 胶壳: 尼龙66, UL94-V0
- ◆ Housing: Nylon66, UL94-V0

	DIM.A	DIM.B	DIM.C
2Y	1.25	2.72	5.72
3Y	2.50	3.97	6.97
4Y	3.75	5.22	8.22
5Y	5.00	6.47	9.47
6Y	6.25	7.72	10.72
7Y	7.50	8.97	11.97
8Y	8.75	10.22	13.22
9Y	10.00	11.47	14.47
10Y	11.25	12.72	15.72
11Y	12.50	13.97	16.97
12Y	13.75	15.22	18.22
13Y	15.00	16.47	19.47
14Y	16.25	17.72	20.72
15Y	17.50	18.97	21.97
20Y	23.75	25.22	28.22
30Y	36.25	37.72	40.72



旭森实业(深圳)有限公司
JUSUN INDUSTRIAL (SHENZHEN) CO.,LTD

GENERAL TOLERANCE

XX. ±0.40	
X. ±0.30	
.X ±0.25	X.° ± 2°
.XX ±0.15	.X° ± 1°

SCALE: 10.5:1

UNIT: mm

SIZE: A4

DRAWN:

CHECK:

APPROVE:

DATE: 7

DATE:

DATE:

DWG. NO. :

E:\DWG\Production\1.25T

PARTS NO. :
1.25T-4-NY

TITLE:

塑胶图

REV. A

SHEET: 1/1