



PCB LAYOUT

孔位	尺寸	
	DIM.A	DIM.B
2	2.00	8.00
3	4.00	10.00
4	6.00	12.00
5	8.00	14.00
6	10.00	16.00
7	12.00	18.00
8	14.00	20.00
9	16.00	22.00
10	18.00	24.00
11	20.00	26.00
12	22.00	42.00
20	38.00	44.00

技术要求:

1 电气性能:

- 1-1 额定电压: 250V DC/AC;
- 1-2 额定电流: 2.0A;
- 1-3 接触电阻: ≤20mΩ;
- 1-4 绝缘电阻: ≥1000MΩ;
- 1-5 耐压: 800V, AC/minute.

2、温度范围: -25℃~85℃;

3、塑胶表面平整、光洁、无毛刺、气泡、变形、浇口无拉伤、缺料等不良现象

4、端子表面无氧化、电镀不良等现象

5、环境管控:

- 5-1. 禁止使用含有SS-00259所限制的物质。
- 5-2. 对应的SGS或ITS出具的ICP-AES数据、不可测定物质的成分表在一年有效期内。

③	焊片	n	黄铜	镍底, 镀锡	GP PASS
②	底座	1	PA9T米色	UL 94V-0	GP PASS
①	插针	n	黄铜	镍底, 镀锡	GP PASS
序号	零件名称	数量	材质	镀涂	REMARK

JUSUN 钜赛实业(深圳)有限公司
JUSAI INDUSTRIAL (SHENZHEN) CO.,LTD

INTENDED USED PART NAME: PH2.0T-3-nAB		DRAWING BY	
INTENDED USED PART NO.:		CHECKED BY	
DRAWING NO: 137-1A-001		APPROVED BY	
SCALE	NONE	REV.	B

UNLESS OTHERWISE SPECIFIED TOLERANCES ARE	
X.	±0.3
.X	±0.2
.XX	±0.15
ANG.	±1'
UNIT	mm

NO.	REV.	图面修改	2016.05.03
A		NEW RELEASE	2016.04.05
NO. REV.		REVISIONS	CHK. DATE