



www.szjusun.cn

NOTES:

1. Dim To Be Checked By QC
2. Along any Portion of strip, Max Allowable Camber is 0.04mm Per 1000mm Length And MAX Allowable Twist is 45° Per 1000mm Length.
3. All Corners and Radii have a maximum Radius of 0.1mm unless Otherwise Specified.

◆外観検査:

1. 端子刮伤
2. 毛边
3. 歪斜变形
4. 电镀颜色

◆打样来料:

1. 塑胶剥胶
2. 端子外覆松劲
3. 内/外/人

◆端子料号:

EL-T
端子:T

◆料原: 磷青铜 (Phosphor Bronze CS191R-B)

◆搭配塑胶: EL-nP

<p>恒泰实业(深圳)有限公司 JUSUN INDUSTRIAL (SHENZHEN) CO.,LTD</p>		GENERAL TOLERANCE		SCALE	DRAWN		DATE	DWG. NO.		TITLE	REV.
		XX. ± 0.25	XXX' ± 40'	5=1	CHECK	DATE	G:\DWG\Production\EL-na.DWG		A		
		X. ± 0.20	XX.' ± 10'	UNIT	CHECK	DATE	PARTS NO.		EL-T(外壳端子)	SHEET	
		.XX ± 0.15	X.' ± 2'	MM	APPROVE	DATE	EL-T(外壳端子)			1/1	
		.XX ± 0.08	X.' ± 1'	SIZE		DATE					