



www.szjustun.cn

Roles	Part No	Dimension(mm)			
		A	B	C	D
2	EL-2A	4.5	0	5.6	10.3
3	EL-3A	9.0	0	5.6	14.8
4	EL-4A	13.5(4.5)	0(4.5)	5.6(10.5)	19.3(10.5)
6	EL-6A	9.0	4.5	10.1	14.8
9	EL-9A	9.0	9.0	14.6	14.8
12	EL-12A	13.5	9.0	14.6	19.3
15	EL-15A	18.0	9.0	14.6	23.8

技术参数 SPECIFICATIONS

- ◆ 间距: 4.5 Pitch: 4.5
- ◆ 适用线规: A WG#24-#16
Applicable Wire: A WG#24-#16
- ◆ 额定电压: AC/DC: 300V(有效值)
Voltage rating: AC/DC: 300V(rms)
- ◆ 额定电流: 6.0-10.0A
Current rating: 6.0-10.0A
- ◆ 耐压值: 1500V AC/minute
Withstand voltage: 1500V AC/minute
- ◆ 工作温度: -25°C~+85°C
Working Temperature: -25°C~+85°C
- ◆ 绝缘电阻: >1000 MΩ
Insulation resistance: >1000MΩ
- ◆ 接触电阻: < 0.015 Ω
Contact resistance: < 0.015 Ω
- ◆ 适用印制板厚度: 1.6-2.0mm
Applicable PC board thickness: 1.6-2.0mm

材料 MATERIAL

- ◆ 绝缘座: 尼龍 UL94-0
Housing: Nylon UL94-0
- ◆ 端子: 磷青銅
Terminal: Phosphor bronze

 恒美实业(深圳)有限公司 JUSAI INDUSTRIAL (SHENZHEN) CO.,LTD		GENERAL TOLERANCE		SCALE		DRAWN		DWG. NO.		TITLE		REV.	
		XX. ± 0.40	XXX. ±	UNIT	1 = 1	CHECK	DATE	G:\DWG\Production\EL-nA		EL-nA		A	
X. ± 0.25	.XXX ±	SIZE	MM	APPROVE	DATE	PARTS NO.		EL-nA		SHEET		1/1	
.X ± 0.15	X' ± 2'												
.XX ± 0.10	X' ± 1'												