



- 技术参数 SPECIFICATIONS
- ◆ 间距: 5.08 Pitch: 5.08
 - ◆ 极数: 4 Poles: 4
 - ◆ 适用线规: AWG#14~#22
 - ◆ Applicable Wire: AWG#14~#22
 - ◆ 额定电压: 250V DC,AC(rms)
 - ◆ Rated voltage: 250V DC,AC(rms)
 - ◆ 额定电流: 10A(AWG#14)
 - ◆ Rated Current: 10A(AWG#14)
 - ◆ 耐压值: 1500V AC/minute
 - ◆ Withstand voltage: 1500V AC/min.
 - ◆ 工作温度: -25°C ~ +90°C
 - ◆ Working Temp : -25°C ~ +90°C
 - ◆ 绝缘电阻: ≥1000 MΩ
 - ◆ Insulation resistance: ≥1000 MΩ
 - ◆ 接触电阻: ≤25mΩ
 - ◆ Contact resistance: ≤25mΩ

■ 材料 MATERIAL
 ◆ 塑胶: 尼龙66 (Nylon66), UL94-V2

		GENERAL TOLERANCE		SCALE: 2.5:1		DRAWN:		DATE:		DWG. NO. :		TITLE:		REV.	
XX	±0.25	XXX	±0.40	UNTT:	mm	CHECK:		DATE:		E:\DWG\Production\		塑胶图	A		
X	±0.20	.XXX	±0.05	SIZE:	A4	APPROVE:		DATE:		PARTS NO. :	大四P-4P			SHEET:	1/1
X	±0.15	X°	± 2°												
.XX	±0.08	X°	± 1°												

炬舜实业(深圳)有限公司

 JUSUN INDUSTRIAL (SHENZHEN) CO.,LTD