



www.szjusun.cn

- 技术参数 SPECIFICATIONS
- ◆ 间距: 5.08 Pitch: 5.08
 - ◆ 极数: 4 Poles: 4
 - ◆ 适用线规: AWG#14~#22
 - ◆ Applicable Wire: AWG#14~#22
 - ◆ 额定电压: 250V DC,AC(rms)
 - ◆ Rated voltage: 250V DC,AC(rms)
 - ◆ 额定电流: 10A(AWG#14)
 - ◆ Rated Current: 10A(AWG#14)
 - ◆ 耐压值: 1500V AC/minute
 - ◆ Withstand voltage: 1500V AC/min.
 - ◆ 工作温度: -25°C ~ +90°C
 - ◆ Working Temp: -25°C ~ +90°C
 - ◆ 绝缘电阻: ≥1000 MΩ
 - ◆ Insulation resistance: ≥1000 MΩ
 - ◆ 接触电阻: ≤25mΩ
 - ◆ Contact resistance: ≤25mΩ

- 材料 MATERIAL
- ◆ 塑胶: 尼龙66 (Nylon66), UL94-V2

GENERAL TOLERANCE		SCALE: 3:1		DRAWN:	
XX ±0.25	XXX ±0.40	UNIT: mm		DATE:	
X ±0.20	XXX ±0.05	CHECK:		DATE:	
X ±0.15	X° ± 2°	SIZE: A4		DATE:	
.XX ±0.08	X° ± 1°	APPROVE:		DATE:	
DWG. NO. : E:\DWG\Production\			TITLE: 塑胶图		
PARTS NO. : 大四P-4Y			REV.: A		
SHEET: 1/1					

炬森实业(深圳)有限公司

 JUSAI INDUSTRIAL (SHENZHEN) CO.,LTD