



www.szjusun.cn

NOTES:

1. Dim To Be Checked By QC
2. Along any Portion of strip, Max Allowable Camber is 0.04mm Per 1000mm Length And MAX Allowable Twist is 45° Per 1000mm Length.
3. All Corners and Radiall have a maximum Radius of 0.1mm unless Otherwise Specified.

◆外观检验:

1. 端子刮伤
2. 毛边
3. 歪针变形
4. 电镀颜色

◆打样夹配:

1. 塑胶裂胶
2. 端子外露松动
3. 内八/外八

◆端子料号:

L6.2-T
端子: T

◆材质: 磷青铜 (Phosphor Bronze C5191R-H)

◆搭配塑胶: L6.2-nA

		巨尚实业(深圳)有限公司 JUSUN INDUSTRIAL (SHENZHEN) CO.,LTD		GENERAL TOLERANCE		SCALE		DRAWN		DATE		DWG. NO.		TITLE		REV.	
XX. ± 0.25	XXX' ± 40°	UNIT	5=1	CHECK	DATE	G:\DWG\Production\L6.2-nA.DWG	L6.2-AT(A座端子)	端子图	A	PARTS NO.		SHEET		1/1		1/1	
X. ± 0.20	XX' ± 10°	MM	APPROVE	DATE	L6.2-AT(A座端子)	1/1											
.X ± 0.15	X' ± 2°	SIZE	A4	DATE													
.XX ± 0.08	X' ± 1°																

A

B

C

D

E

A

B

C

D

E

3

2

1

3

2

1