



www.szjusun.cn

技术参数 SPECIFICATIONS

- ◆ 间距: 6.2 Pitch: 6.2
- ◆ 适用线规: AWG#24-#14  
Applicable Wire: AWG#24-#14
- ◆ 额定电压: AC,DC,300V(有效值)  
Voltage rating: AC,DC,300V(rms)
- ◆ 额定电流: 10.0A  
Current rating: 10.0A
- ◆ 耐压值: 1500V AC/minute  
Withstand voltage: 1500V AC/minute
- ◆ 工作温度: -25°C~+85°C  
Working Temperature: -25°C~+85°C
- ◆ 绝缘电阻: ≥1000 ohm  
Insulation resistance: ≥1000ohm
- ◆ 接触电阻: < 0.02 oh  
Contact resistance: < 0.02 oh

材料 MATERIAL

- ◆ 绝缘座: 尼龍 UL94-0  
Housing: Nylon UL94-0
- ◆ 端子: 磷青铜  
Terminal: Phosphor bronze

Poles	Part No	Dimensions(mm)	
		A	B
2	L6.2-2Y	6.2	13.3
3	L6.2-3Y	12.4	19.5

**JUSUN**  
**旭森实业(深圳)有限公司**  
 JUSAI INDUSTRIAL (SHENZHEN) CO.,LTD

GENERAL TOLERANCE		SCALE		DRAWN		DATE		DWG. NO.		TITLE		REV.	
XX. ± 0.40	XXX. ±	1	= 1	CHECK		DATE		G:\DWG\Production\L6.2-nY		塑膠座	A		
X. ± 0.25	.XXX ±	UNIT	MM	APPROVE		DATE		PARTS NO.	L6.2-nY		SHEET		
X ± 0.15	X. ± 2'	SIZE	A4			DATE					1/1		
.XX ± 0.10	X' ± 1'												

A B C D E

1 2 3