



www.szjusun.cn

NOTES:

1. Dim To Be Checked By QC
2. Along any Portion of strip, Max Allowable Camber is 0.04mm Per 1000mm Length And MAX Allowable Twist is 45° Per 1000mm Length.
3. All Corners and Radll have a maximum Radius of 0.1mm unless Otherwise Specified.

◆外观检验: 1. 端子刮伤

2. 毛边

3. 歪斜变形

4. 电镀颜色

◆打样装配: 1. 塑胶裂胶

2. 端子外露松动

3. 内八/外八

◆端子料号: L6.2-T



◆料质: 磷青铜 (Phosphor Bronze C5191RH)

◆搭配塑胶: L6.2-nY

<p>巨森实业(深圳)有限公司 JUSAI INDUSTRIAL (SHENZHEN) CO.,LTD</p>		<p>GENERAL TOLERANCE</p> <table border="1"> <tr> <td>XX. ± 0.25</td> <td>XXX' ± 40°</td> </tr> <tr> <td>X. ± 0.20</td> <td>XX.' ± 10°</td> </tr> <tr> <td>.X ± 0.15</td> <td>X.' ± 2°</td> </tr> <tr> <td>.XX ± 0.08</td> <td>.X' ± 1°</td> </tr> </table>		XX. ± 0.25	XXX' ± 40°	X. ± 0.20	XX.' ± 10°	.X ± 0.15	X.' ± 2°	.XX ± 0.08	.X' ± 1°	<p>SCALE 5=1</p> <p>UNIT MM</p>		<p>DRAWN</p> <p>CHECK</p> <p>APPROVE</p>		<p>DATE</p> <p>DATE</p> <p>DATE</p>		<p>DWG. NO.</p> <p>G:\DWG\Production\L6.2-nA.DWG</p>		<p>TITLE</p> <p>端子图</p>		<p>REV.</p> <p>A</p>	
XX. ± 0.25	XXX' ± 40°																						
X. ± 0.20	XX.' ± 10°																						
.X ± 0.15	X.' ± 2°																						
.XX ± 0.08	.X' ± 1°																						
<p>SIZE A4</p>		<p>DATE</p>		<p>PARTS NO.</p> <p>L6.2-YTY(座端子)</p>		<p>SHEET</p> <p>1/1</p>																	

A B C D E

3 2 1 3 2 1 3