



PCB LAYOUT

www.szjusun.cn

SPECIFICATIONS

- 1、Current Rating: 3A AC, DC
- 2、Voltage Rating: 250V AC, DC
- 3、Temperature Range: -25°C~+85°C
- 4、Contact Resistance: 20mΩ Max
- 5、Insulation Resistance: 1000MΩ Min
- 6、Withstanding Voltage: 1000V AC/minute
- 7、Material: Wafer LCP, PA6T, UL94V-0
PIN Brass Tin-plated
Solder tad Phosphoric bronze Tin-plated

编号	尺寸 (mm)		
	A	B	C
A25011F-02A	2.50	7.50	10.00
A25011F-03A	5.00	10.00	12.50
A25011F-04A	7.50	12.50	15.00
A25011F-05A	10.00	15.00	17.50
A25011F-06A	12.50	17.50	20.00
A25011F-07A	15.00	20.00	22.50
A25011F-08A	17.50	22.50	25.00
A25011F-09A	20.00	25.00	27.50
A25011F-10A	22.50	27.50	30.00
A25011F-11A	25.00	30.00	32.50
A25011F-12A	27.50	32.50	35.00
A25011F-20A	47.50	52.50	55.00

制图	DATE	GENERAL TOLERANCE	DATE	DESCRIPTION	DRAWN
审核		X.±0.25			
核准		.X±0.15			
批准		.XX±0.5*			
APPROVAL		.XXX±0.10			
UNIT		.XXX±0.5*			

料号	品名	客户料号	版本
PART NO.	TJCS立贴	客户料号	REV.
	WAFFER SWT TYPE		A
			1/1