



www.szjusun.cn

PCB LAYOUT

- SPECIFICATIONS
- 1、Current Rating: 3A AC, DC
  - 2、Voltage Rating: 250V AC, DC
  - 3、Temperature Range: -25°C~+85°C
  - 4、Contact Resistance: 20mΩ Max
  - 5、Insulation Resistance: 1000MΩ Min
  - 6、Withstanding Voltage: 1000V AC/minute
  - 7、Material: Wafer LCP, PA6T, UL94V-0  
PIN Brass Tin-plated  
Solder tad Brass Tin-plated

编号	尺寸 (mm)		
	A	B	C
A2501WF-02A	2.50	7.50	10.00
A2501WF-03A	5.00	10.00	12.50
A2501WF-04A	7.50	12.50	15.00
A2501WF-05A	10.00	15.00	17.50
A2501WF-06A	12.50	17.50	20.00
A2501WF-07A	15.00	20.00	22.50
A2501WF-08A	17.50	22.50	25.00
A2501WF-09A	20.00	25.00	27.50
A2501WF-10A	22.50	27.50	30.00
A2501WF-11A	25.00	30.00	32.50
A2501WF-12A	27.50	32.50	35.00
A2501WF-20A	47.50	52.50	55.00

制图	变更内容	日期	GENERAL TOLERANCE		制图
			DATE	DESCRIPTION	
DRW			X.±0.25	X.±2°	审核
			.X±0.20	X.±1°	检查
			.XX±0.15	.XX±0.5°	核准
			.XXX±0.10	.XXX±0.5°	批准
					APPROVAL
					UNIT
					MM
					SCALE
					1:1

料号 PART NO. A2501WF-NA  
 品名 贴片 T JCG3  
 TITLE WAFER SMT TYPE  
 客户料号  
 QTY. NO.

版本 REV. A  
 页次 1/1  
 SHEET

**JUSUN** 炬赛实业(深圳)有限公司  
 JUSAI INDUSTRIAL (SHENZHEN) CO.,LTD